TECHNICAL DATA SHEET



Product Code: 8146 Sector: Automotive (Passenger Car & LCV) Issue No: 3 Issue Date: 01/02/24

TRIDENT PROFESSIONAL ENGINE OIL C1 5w30

Fully synthetic, low SAPS, for use in petrol, diesel and hybrid engines.

Application

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a C1 5w30 viscosity targeting Jaguar Land Rover vehicles fitted with DPFs.

Performance Profile

ACEA C1

Suitable for

Ford WSS-M2C934-B Jaguar Land Rover STJLR.03.5005 JASO DL-1 Asian manufacturers

Features & Benefits

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which improves fuel economy, reduces emissions and provides extended drain capability.
- Utilising low SAPS technology protecting particulate filters and controlling soot build up.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

Typical Characteristics

Density @ 15°C, g/ml 0.844 Kinematic Viscosity @ 100°C, cSt. 10.5 Flashpoint, °C >200

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: SAPS - Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer